## #1260NR

# NATURAL RUBBER PREMIUM BOPP PACKAGING TAPE

### **QRAMO MATERIALS**

## **TECHNICAL DATA SHEET**

#### **DESCRIPTION**

A rugged biaxially-oriented polypropylene (BOPP) film coated with an aggressive pressure sensitive solvent natural rubber adhesive designed especially for dependable closure of corrugated and linerboard boxes. Natural rubber tapes offers fast, positive bonding on problematic applications such as high recycled content cartons, rough or ultra-smooth cartons, heavy ink coverage, dusty and/ or dirty environments, humid conditions and temperatures extremes.

#### **PRODUCT APPLICATIONS**

Heavy duty box sealing and packaging applications exposed to rougher or more challenging shipping hazards and stress. Best used for frozen food and fruits packaging which operate under extreme temperatures in work areas such as freezers & cold rooms. Ideal for rough and dusty environments such as garment and fabric manufacturing facilities etc.

#### **ALTERNATIVE TO:**

Unitape, Panfix, Uta & Polyseal



Qramo Materials Co., Ltd. บริษัท คราโม่แมททีเรียลส์ จำกัด

133 Rom Klao Soi 27,

Lat Krabang, Bangkok 10520

Phone : (66)-2-734-4440 Fax : (66)-2-734-4450 Website : www.qramo.com

#### **NOMINAL VALUES**

The following data are based on nominal values based on PSTC, ASTM and other industry standard tests. The data should not be considered as specifications.

**Backing** (Cast Film) BOPP Film

Adhesive Natural Rubber

**Total Thickness** 0.060mm

**180 °Peel Adhesion** (SUS) 10.60 (N/25mm)

ASTM D-3330

**Tensile Strength** (at break) 92.60 (N/25mm)

**ASTM D-3759** 

**Holding Power** 0.054 (mm/hr)

ASTM D-3654 (1kg, 80°C)

**Elongation** (at break) 180%

ASTM D-3759

Colour

**Temperature Range**-35°C to +93°C
(Operating)

-35°C to +93°C
(-31°F to +200°F)

Clear, Brown



While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees or accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. QRAMO MATERIALS MAKE NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. This product will be free from defects in material and workmanship at time of shipment. If this product is defective, your exclusive remedy and Qramo's sole obligation shall be, at Qramo's option, to replace the product or refund the purchase price. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. Copyright © 2019 Qramo Materials. All rights reserved.